

# MATERIAL SAFETY DATA SHEET

MANUFACTURER'S NAME:

STEWART BROS. PAINT CO.  
1010 N. UNION AVE., P.O. BOX 2208  
ALLIANCE, OHIO 44601-0208

DATE OF PREPARATION: 11-20-1995

EMERGENCY TELEPHONE NO.:

1-800-424-9300

INFORMATION TELEPHONE NO.:

1-216-821-1050

---

## SECTION I - PRODUCT IDENTIFICATION

---

PRODUCT NUMBER:	10593	HMIS RATINGS:	H	F	R	PP
PRODUCT NAME:	10593 CHARCOAL MET. AIR DRY EN		2	3	0	G
PRODUCT CLASS:	VINYL TOLUENE ALKYD					

---

## SECTION II - HAZARDOUS INGREDIENTS

---

INGREDIENT	CAS NUMBER	WEIGHT PERCENT	OCCUPATIONAL EXPOSURE LIMITS	VAPOR PRESSURE mm Hg @ TEMP	
VM&P NAPHTHA	64742-89-8	45	300 PPM	15.0	45C
XYLOL	1330-20-7	< 5.0%	100 PPM	5.1	20C
+ ALUMINUM PASTE	7429-90-5	< 5.0%	N/A	0.0	20C
MINERAL SPIRITS	8052-41-3	< 0.5%	100 PPM	2.0	20C
COBALT CARBOXYLATE	N/A	< 0.5%	N/A	0.0	20C
ZIRCONIUM COMPOUNDS	7440-67-2	< 0.5%	N/A	0.0	20C
METHYL ETHYL KETOXINE	95-29-7	< 0.5%	N/A	1.1	20C
TRIETHYLAMINE	121-44-8	< 5.0%	25	54.0	20C
METHANOL	67-56-1	< 5.0%	200	97.0	20C
HI SOL 10	64742-95-6	< 0.5%	100 PPM	3.0	20C
HI SOL 15	64742-95-6	< 0.5%	100 PPM	5.0	45C

---

## SECTION III - PHYSICAL DATA

---

BOILING RANGE: 240-280 F

VAPOR DENSITY: HEAVIER THAN AIR

EVAPORATION RATE: SLOWER THAN ETHER    % VOLATILE VOLUME: 66.84    WT/GAL: 6.81